

The all new and perfected IQ Quattro X is a must have for every

Faster: IQ Quattro X is the 5th generation of Contex CIS scanners, with enhanced speed and 3 times faster data transfer, the scanner is the essence of productivity.

Smarter: The Nextimage Remote app offers you a completely new way of working. The new app saves valuable operator time by bringing all main functions essential for basic scanning and copying in front of the operator directly on the scanner.

Better: Contex Live Alignment is a new IQ Quattro X technology designed to improve image alignment across sensors ensuring precise and sharp alignment all the time, no matter the speed.

Improved technology: Contex USB 3.0 implementation with xDTR3 is blisteringly fast and you won't have to worry about shoe shining or rescanning to get the width right.

Image quality

The 48-bit CIS technology captures every detail from your document, then passes the best 24-bits through to the file at up to 1200 dpi optical resolution.

Fastest CIS scanner

The IQ Quattro X scanners produce a scan speed of up to 17.8 inches per second in RGB color and 200 dpi.

3-position speed control

Great for use with delicate originals. Temporarily shift down to slower scan speeds without using presets or altering software.

Green technology

Energy Star® version 3.0 compliant using only 0.5W in standby mode.

High productivity

Enhanced speed and data transfer rates makes the IQ Quattro X the essence of productivity.

OUTSTANDING IMAGE QUALITY AND PRODUCTIVITY

SEE MORE: contex.com/igguattrox

high-production environment.






	IQ QUATTRO X 4450	IQ QUATTRO X 4490
Maximum scan width	44 inch (1118 mm)	
Maximum media width	47 inch (1194 mm)	
Scanning speed1 (inch/sec.) 36-incl	n wide document	
200 dpi RGB color	8.9	17.8
Upgradeable to 17.8 inch/sec color	Upgradeable	Included
200 dpi grayscale/monochrome	17.8	17.8
Productivity (documents/hour) Bato	ch scanning for 60 minutes. Includes paper load and eject	time. Measured in completed scans
Arch E-size, portrait, monochrome/RGB color, 200 dpi	523	856
Specifications		
Maximum media thickness	0.08 in (2 mm) flexible documents	
Optical resolution	1200 dpi	
Maximum resolution	9600 dpi (interpolated)	
Total number of pixels	64800 pixels	
Contex key CIS technologies	CleanScan ² , SIGMA ³ , CFR ⁴	
Document justification	Flexible center load, due to autosize	
Accuracy	0.1% +/- 1 pixel	
Data capture color depth	48-bit color/16-bit monochrome	
Color spaces	Adobe RGB, Device RGB, RAW RGB, sRGB	
USB connection	USB 3.0 with xDTR3	
Ethernet connection	Gigabit with xDTR2.5	
Networking protocols	Push and pull	
Energy Star®5	Yes, version 3.0	
Included software ⁶	Nextimage TWAIN, Nextimage Remote tablet app (free download for iOS and Android), WIDEsystem (driver)	
Optional software	Nextimage 5	
File formats ⁷	TIF, JPG, PDF, PDF/A, DWF, CALS, BMP, JPEG-2000(JP2), JPEG2000 Extended (JPX), TIF-G3, TIF-G4 and others	
File compatibility	AutoCAD®, Microstation™, ArcGIS™ and all other CAD, GIS and other image editing/storage applications	
Printer support ⁷	HP, Canon, Epson and Océ printers. See contex.com/nextimage-supported-printers for full list	
Operating systems	Windows Server 2019 64-bit, Windows 10 and Windows 8.1, 64-bit + 32 bit	
Power consumption (ready/sleep/scan)	18W max. / <1W / 37W (built-in power supply)	
Power supply	100-240 V, 60/50 Hz	
Weight	54 lbs (24.5 kg)	
Dimensions	53.1×19.3×6.3 in (1349×489×161 mm)	
Certifications/compliance	CE, cUL/UL, CCC, EAC, UKR, BIS, FCC Class A, ICES, EMC, VCCI, KC, EuP, WEEE, RoHS, REACH and ENERGY STAR® certified	
Country of origin	Designed and engineered in Denmark, Europe. Manufactured in China.	
Scanner stand (optional)	Low adjustable stand (3 settings): 32.6/33.8/34.8 in (827/859/884 mm) High adjustable stand (9 settings): 43 to 50.9 inches in steps of 1 inch (1092 to 1292 mm in 25 mm steps)	
ScanStation Pro compatibility	Yes	

- 1. Test equipment: Nextimage 5 software, Intel Core i7 4770K 3.5 GHz ,16 GB RAM, 1TB SSD, SuperSpeed USB 3.0 PC, Win 64-bit
- Minimum computer: Intel Core Duo, Core 2 Duo or better 64-bit processor, 8 GB RAM, SSD SATA hard drive, Win 64-bit Contex CleanScan is a Contex innovation comprising dual-sided and dual-diffused LEDs in a single custom-built CIS module Contex Signal Intensity Matching (SIGMA) is a Contex patent that reduces the effects of uneven heat build-up in CIS sensors during scanning
- Contex Color Fringe Removal (CFR) is a Contex patent that sharpens images by filtering out the fringes produced by strobing CIS devices
- Energy Star® version.3.0. Introduced October 2019
- Nextimage TWAIN relies on the external host software to print, copy and save scanned information
- Nextimage scanning software required


Tablet not included.

All trademarks remain the property of their respective holders, and are used only to directly describe the product being provided. Their use does not indicate a relationship between Contex and the trademark holders.

IQ Quattro X: High data transfer - superior image quality



Contex CleanScan CIS The IQ Quattro Scanners are equipped with Contex CleanScan CIS modules which facilitate optical image quality with dual-sided LED lighting. This eliminates creases and folds in originals normally a challenge for CIS scanners, and thus provides clear, crisp scans every time.



Color fringe removal (CFR) technology Color Fringe Removal (CFR) is an

advanced Contex patented filtering technology designed to remove the fringes inherent in CIS strobing scanning devices.

Contex solutions are compatible with all leading large-format printers. See the full list at contex.com/nextimage-supported-printers













contex.com/iqquattrox

